

INDIA'S #1 GENSET BRAND

PETROL & DIESEL KG PORTABLE GENSETS

2.1 - 5 kVA



Kirloskar Green Offerings

- Fuel Efficient
- Easy Key Start[#]
- Easy Maneuverability
- Widest Service Network
- Controller Based Monitoring^{*}
- Stable Output With Silent Design
- Highest Rated Power Output
- 24 x 7 Customer Support

EFFICIENCY HAS A NEW NAME

Kirloskar
GREEN

[#] Available only in Petrol variant genset

^{*} Available only in Diesel variant genset

Technical Specifications

		DIESEL GENSET			PETROL GENSET			
Rated Output at 230V / 50Hz	kVA*	3.5	5	5				
Rated Output at 230V / 50Hz	kW ^{ss}	2.8	4	4	2.1	3	4	
Max Out Put	kVA	3.85	5.5	5.5	2.4	3.3	5***	
Genset model		CC1-3.5AS4 [#]	CC1-5AS4 [#]	CC1-5AS2 ^o	KCC-P-2.1 AS	KCC-P-3.0 AS	KCC-P-4.0 AS	
Rated current at Unity PF	A	12.17	17.39	17.39	9.13	13	17.39	
Voltage	V	230, Single phase (with AVR type technology)			230, Single phase (with AVR type technology)			
Noise level (1M) - for reference	dBA	≤ 75	≤ 75	≤ 70	71	71	71	
Fuel consumption**	At 100 % load	Ltrs/hr	1.11	1.5	1.5	1.29	1.9	2.7
	At 75 % load		0.93	1.2	1.2	1.09	1.5	2.1
	At 50 % load		0.78	0.9	0.9	0.84	1.3	1.6
Fuel tank capacity	Ltrs	12.5	12.5	13	6.5	12.5	12.5	
Overall dimensions of genset (L x W x H) [^]	mm	1150 x 560 x 840	1150 x 560 x 840	970 x 580 x 970	950 x 510 x 650	1045 x 550 x 735	1045 x 550 x 735	
Weight of genset with canopy approx. [^]	Dry	kg	190	190	190	110	129	145
			ENGINE					
Engine model		CC418 G1	CC418 G1	CC418 G1	CCP196	CCP302	CCP389	
Rated output (Prime continuous rating as per ISO 3046)	kW	5.5	5.5	5.5	2.9	4.2	5.6	
	HP	7.47	7.47	7.47	3.94	5.7	7.6	
Cubic capacity	cc	418	418	418	196	302	389	
Lube oil change period [§]	Hrs	200	200	200	100	100	100	
Lube oil sump capacity	Ltrs	1.65	1.65	1.65	0.6	1.1	1.1	

Above Gensets are single cylinder, air cooled with 50 Hz frequency, 230V single phase, 12V battery and 3000 rpm as standard features | Recoil start also available with selected gensets
[^] Tolerances apply | [#]Genset model will be available in 4 wheel configuration | ^oGenset model will be available in 2 wheel configuration | * Max kW for petrol gensets & kVA for diesel gensets
[§] ** With 0.845 specific gravity of diesel (5% tolerance) | For Air Conditioning load, kindly contact authorised KOEL Green sales expert | [§]At NTP | ^{ss} Rated kW for petrol gensets | ***For limited time



India's #1 Genset brand

- Over 1 million Gensets in service across the globe
- Specialised genset manufacturer for more than seven decades; offers a wide range of power solutions upto 1010 kVA



Kirloskar Green Solution

- Revolutionary sound absorption system makes the owner totally relaxed during power cut
- Complies with the latest noise regulation and emission norms



Widest well-trained service network

- Supported by over 5000 skilled engineers and over 450 well-equipped service outlets
- Centrally monitored service quality and response time
- Dial customer support and our authorized representative will be at your door step!



Complete solution with AMFi Panels

- Switch on automatically
- High reliability
- Ready to start with built-in battery charger
- Easy to mount and install



Widest product range

- Choice of power is now unlimited, choose from 2.1 kW till 5 kVA in petrol or diesel
- Choose genset from the widest range as per your ideal power needs



Enjoy the benefits of mobility and portability

- Kirloskar Green rolls on wheels and is equipped with a wide length handle
- Carry power with you for a beach party or a jungle camp
- Great help for small establishments and mobile workshops too!

* AMF Panel is available only for diesel variants of KCC Portable Gensets

Why get satisfied with power back-up of 4 lights & 4 fans ?

With Kirloskar Green Gensets ensure non stop comfort of wide range of appliances

COMPUTER / LAPTOP

LED TELEVISION

WASHING MACHINE

AIR CONDITIONER

REFRIGERATOR

COLD DRINK REFRIGERATOR

DEEP FREEZER



www.koel.kirloskar.com
Kirloskar Oil Engines Limited
 A Kirloskar Group Company
 Laxmanrao Kirloskar Road, Khadki,
 Pune 411 003 INDIA.
88 06 33 44 33
koel.helpdesk@kirloskar.com

